




iPod Touch 5th Generation Battery Replacement

Prerequisite only, loosen the battery from the rear case.

Written By: Andrew Optimus Goldberg



INTRODUCTION


Prerequisite only, loosen the battery from the rear case.



TOOLS:


- [iFixit Opening Tools](#) (1)
 - [Suction Handle](#) (1)
 - [Phillips #000 Screwdriver](#) (1)
-

Step 1 — Battery



- Remove three 1.6 mm #000 Phillips screws securing the logic board to the rear case.

Step 2 — Warm back of iPod with heat gun or hair dryer



- There are two strips of adhesive keeping the battery in place.
- Turn the iPod over and heat the **BACK** of the aluminium iPod case. *Do not heat the battery.*
- The aluminium case does **not** have to be hot; you should always be able to touch heated parts with your fingers at all times without it being uncomfortable.



Step 3



- i** There are three notches on either side of the battery. In the next few steps, you will be using these notches to gradually pry the battery up from the rear case.
- i** The battery is secured with large amounts of adhesive, so you'll need to go slowly and carefully to avoid puncturing or creasing the battery.



 - Insert a plastic opening tool into the top right notch and gently pry up on the battery.
- !** Do not attempt to pry up the entire battery at this point; you just want to start to loosen the adhesive at each of the prying points, in turn.

Step 4




- Continue with the lower right notch. Insert the plastic opening tool into the notch, and gently pry up on the side of the battery.


Step 5



- Continue prying the battery up from the bottom.


 When prying along the bottom, be careful not to press down too hard against the speaker or headphone jack.

Step 6



- Pry along the left side as well.
- ⓘ You may need to move back and forth between the sides and bottom of the battery, prying a small amount at a time until the battery is entirely free from the adhesive.

Step 7



- Once all of the adhesive is loosened, lift the battery up from the bottom and swing it out over the left side of the rear case.
- ⚠ Be sure not to yank it out, as it is soldered to the logic board.
- Flip the battery over to straighten its cable and set it down.

To reassemble your device, follow these instructions in reverse order.

This document was last generated on 2017-11-26 10:54:59 PM.